

# TEKNIC

CE 

Control and Signaling Devices Ø 22.5 Clip on Plastic Series  
MRP with effect from 01.11.2021



## Control and signaling devices Ø 22.5 P4 Clip on series

### Salient features

This range of Ø 22.5 P4 Clip on series pushbuttons, selector switches, illuminated switches and pilot lights in engineering plastic construction have been designed to provide the following salient features:


- Economy of space
- Aesthetically elegant
- Robust in materials of construction
- Simple to fix-Snap fitting
- Safe in operation
- Fixing method unaffected by excessive vibration unit does not rotate
- Very good flame resistance
- Shrouded terminals
- Protection against electrical shock
- Resistant to corrosion

### Actuators

The circular actuators have black plastic bezels, and are functionally interchangeable on the different types of contact elements.

### Contact elements

The contact elements are double break. The elements are interchangeable & can be stacked without additional hardware, 1 to 6 elements (NO or NC) can be used with non illuminated actuators, whereas, 1 to 4 elements (NO or NC) can be used for illuminated actuators. **Gold plated NO and NC contact elements for low voltage, low current switching circuits, < 25 mA, are available. Base mounting elements are also available.**



### Illuminated pushbuttons & pilot lights

Pilot lights and illuminated switches are suitable for direct connection using bayonet cap multi chip LED bulb (with OAL max 28 mm). Supply voltage using Multichip Led Bulb ..... : 12V-230 VAC / DC

Pilot lights and illuminated actuators are available with LED bulbs suitable for operating at various voltages namely 12V, 24V, 110V and 230V AC/DC.

### Terminals

Contact elements and pilot lights are designed to have shrouded terminals with combi screws.



### Fixing

The Ø 22,5 P4 Clip on series control devices can be fixed in any position on panels of 1 to 5 mm thickness.

We recommend minimum fixing centres of 30mm X 40mm. However, the dimensions and configuration should be decided on the basis of the application.

The actuators, and the lense assemblies snap fit on the holding bracket.

Details of the assembly shown in diagram.



### Electrical and mechanical characteristics

#### Environment

Standards conformity	:	UL 508, EN 60947-5-1
Approvals	:	UL 508
Degree of protection	:	IP 65 as per IEC 60529, NEMA 4X, 12 as per UL 50
Ambient	:	- 25°C to + 70°C
Operating position	:	All positions
Pollution Degree	:	3

#### Contact Block

Rated insulation voltage	:	500 V																		
Rated thermal current	:	10 A																		
Contact operation	:	Slow break NO or NC																		
Make and break capacity	:	AC 15 4 A, 415 V AC																		
As per IEC 60947 - 5 - 1	:	DC 13 0.5 A, 110 V DC																		
Terminal capacity	:	Maximum 2 x 1.5 mm <sup>2</sup> or 1 x 2.5 mm <sup>2</sup> .Minimum 1 x 0.5 mm <sup>2</sup>																		
Terminal marking	:	1 - 2 for NC & 3 - 4 for NO																		
Short circuit protection	:	10 A HRC cartridge fuse, rated for resistive loading at 1000 A Prospective Current																		
Mechanical life	:	Over 1 million operations																		
Electrical rating	:																			
(for 1 million operating cycles, operating at 3600 cycles per hour, load factor 0.5)	:																			
		<table border="0"> <tr> <td>AC 15</td> <td>V</td> <td>24</td> <td>120</td> <td>230</td> <td>DC 13</td> <td>V</td> <td>24</td> <td>110</td> </tr> <tr> <td></td> <td>A</td> <td>4</td> <td>3</td> <td>2</td> <td></td> <td>A</td> <td>0.5</td> <td>0.2</td> </tr> </table>	AC 15	V	24	120	230	DC 13	V	24	110		A	4	3	2		A	0.5	0.2
AC 15	V	24	120	230	DC 13	V	24	110												
	A	4	3	2		A	0.5	0.2												
Screw clamp tightening torque	:	0.8 Nm (Nominal recommended)																		

### Modules for pilot light & illuminated switches with LED bulb (BA9S cap)



Current consumptions (applicable to all colours)

24 V AC/DC, 110 VAC & 240 VAC	:	max. 20 mA
Terminal capacity	:	Maximum 2 x 1.5 mm <sup>2</sup> or 1 x 2.5 mm <sup>2</sup> . Minimum 1 x 0.5 mm <sup>2</sup>
Service life (at nominal voltage and at ambient temperature at 25°C)	:	50,000 hours

MRP w.e.f. 01.11.2021

Control & Signalling Devices 22.5 Ø

CLIP ON PLASTIC SERIES





MOMENTARY ACTUATORS				
	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs.
		White	P4AF1	57.50
		Black	P4AF2	57.50
	<b>Flush</b>	Green	P4AF3	57.50
		Red	P4AF4	57.50
		Blue	P4AF6	57.50
		Yellow	P4AF8	57.50
	<b>Flush with Arrow marking</b>	White	P4AF1BA	77.00
		Black	P4AF2WA	77.00
		White	P4AP1	57.50
		Black	P4AP4	57.50
	<b>Projecting</b>	Green	P4AP3	57.50
		Red	P4AP4	57.50
		Blue	P4AP6	57.50
		Yellow	P4AP8	57.50
		White	P4AF1RR	75.00
		Black	P4AF2RR	75.00
	<b>Flush Relay</b>	Green	P4AF3RR	75.00
	<b>Reset Actuators</b>	Red	P4AF4RR	75.00
		Blue	P4AF6RR	75.00
		Yellow	P4AF8RR	75.00
		White	P4AF12BT7	117.50
		Black	P4AF22BT7	117.50
	<b>Booted</b>	Green	P4AF32BT7	117.50
		Red	P4AF42BT7	117.50
		Blue	P4AF62BT7	117.50
		Yellow	P4AF82BT7	117.50

MRP w.e.f. 01.11.2021

Control & Signalling Devices 22.5 Ø

CLIP ON PLASTIC SERIES

MUSHROOM HEAD ACTUATORS

	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs.
				
	Latching	Black	P4AMLS2	126.00
	Ø 30mm	Red	P4AMLS4	126.00
		Black	P4AM2	91.50
	Momentary	Green	P4AM3	91.50
	Ø 40mm	Red	P4AM4	91.50
		Blue	P4AM6	91.50
		Yellow	P4AM8	91.50
				
	Push Pull	Black	P4AMPP4	126.00
	Ø 40 mm	Red	P4AMPP4	126.00
				
	Latching	Black	P4AML2	126.00
	Ø 40mm	Red	P4AML4	126.00
				
	Latching	Black	P4AMLKB2	253.00
	with Key	Red	P4AMLKB4	253.00
	Ø 40mm			

MRP w.e.f. 01.11.2021

Control & Signalling Devices 22.5 Ø

CLIP ON PLASTIC SERIES

MUSHROOM HEAD ACTUATORS

	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs.
	Trigger type	Black	P4AMLT2	189.50
	Press to Lock	Red	P4AMLT4	189.50
	turn to release			
	Ø 40 mm			
	Trigger type	Black	P4AMLTKB2	315.00
	Press to Lock	Red	P4AMLTKB4	315.00
	key to release			
	Ø 40 mm			
		Black	P4AMJ2	124.50
	Momentary	Green	P4AMJ3	124.50
	Ø 60mm	Red	P4AMJ4	124.50
		Blue	P4AMJ6	124.50
		Yellow	P4AMJ8	124.50
		Black	P4AMPPJ2	164.00
	Push Pull	Red	P4AMPPJ4	164.00
	Ø 60 mm			
		Black	P4AMLJ2	164.00
	Latching	Red	P4AMLJ4	164.00
	Ø 60mm			

**MRP w.e.f. 01.11.2021**
**Control & Signalling Devices 22.5 Ø**
**CLIP ON PLASTIC SERIES**
**SELECTOR ACTUATORS**












	TYPE		COLOUR	ORDERING CODE	PRICE IN Rs.	
	Selector		Black	P4AS2-2P	176.00	
	2 position					
	LATCHING					
	with ext. knob					
					P4AS2E-2P	176.00
	2 position		Black	P4AS2-2PSR	176.00	
	MOMENTARY					
	with ext. knob					
	3 position		Black	P4AS2-3P	176.00	
	STAY PUT					
	with ext. knob					
	MOMENTARY		Black	P4AS2-3PSR	190.50	
	on both sides					
	with ext. knob					
	MOMENTARY		Black	P4AS2-3PSRR	190.50	
	on right					
	with ext. knob					
MOMENTARY		Black	P4AS2-3PSRL	190.50		
on left						
with ext. knob						

MRP w.e.f. 01.11.2021





Control & Signalling Devices 22.5 Ø

CLIP ON PLASTIC SERIES

KEY SELECTOR ACTUATORS

	TYPE		COLOUR	ORDERING CODE	PRICE IN Rs.	
	2 Position Stayput		Black	P4AK2-2PB	242.00	
				P4AK2-2PO	242.00	
				P4AK2-2PI	242.00	
				P4AK2-2POSR	242.00	
	3 Position Stayput		Black	P4AK2-3PA	253.00	
				P4AK2-3PB	253.00	
				P4AK2-3PC	253.00	
	Spring Return		Black	P4AK2-3PSR	253.00	
	Right to Centre			P4AK2-3PSRR	253.00	
	Left to Centre			P4AK2-3PSRL	253.00	
	* X stands for position in which key is removable					

**MRP w.e.f. 01.11.2021**  
**Control & Signalling Devices 22.5 Ø**

<b>CLIP ON PLASTIC SERIES</b>				
<b>TWIN ACTUATORS</b>				
	<b>TYPE</b>	<b>COLOUR</b>	<b>ORDERING CODE</b>	<b>PRICE IN Rs.</b>
	Double Flush w/o IO Mark	Green	P4ATF3F4	108.00
		Red		
	Double Flush with IO Mark	Green	P4ATF3F4(IO)	108.00
		Red		
	1 Flush, 1 Projecting w/o IO Mark	Green	P4ATF3P4	108.00
		Red		
	1 Flush, 1 Projecting with IO Mark	Green	P4ATF3P4(IO)	108.00
		Red		





MRP w.e.f. 01.11.2021

Control & Signalling Devices 22.5 Ø

CLIP ON PLASTIC SERIES

ILLUMINATED MOMENTARY ACTUATORS WITH LED BULB




	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs. WITH LED BULB
<b>Illuminated Flush, Momentary</b>				
	LED Bulb, BA9S type	White LED Bulb / White Lens	P4ALF1LB(S)	408.50
	24V AC/DC,	Green LED Bulb / Green Lens	P4ALF3LB	215.00
	110VAC, 110VDC	Red LED Bulb / Red Lens	P4ALF4LB	215.00
	230VAC, 220VDC	Amber LED Bulb / Amber Lens	P4ALF5LB	215.00
		Blue LED Bulb / Blue Lens	P4ALF6LB	432.50
		White LED Bulb / Clear Lens	P4ALF7LB(S)	408.50
		Yellow LED Bulb / Yellow Lens	P4ALF8LB	215.00
<b>LED Bulb</b>	Please mention the voltage required after the ordering code			
<b>Illuminated Projecting, Momentary</b>				
		White LED Bulb / White Lens	P4ALP1LB(S)	408.50
	LED Bulb, BA9S type	Green LED Bulb / Green Lens	P4ALP3LB	215.00
	24V AC/DC,	Red LED Bulb / Red Lens	P4ALP4LB	215.00
	110VAC, 110VDC	Amber LED Bulb / Amber Lens	P4ALP5LB	215.00
	230VAC, 220VDC	Blue LED Bulb / Blue Lens	P4ALP6LB	432.50
		White LED Bulb / Clear Lens	P4ALP7LB(S)	408.50
		Yellow LED Bulb / Yellow Lens	P4ALP8LB	215.00
<b>LED Bulb</b>	Please mention the voltage required after the ordering code			

MRP w.e.f. 01.11.2021

Control & Signalling Devices 22.5 Ø

CLIP ON PLASTIC SERIES

ILLUMINATED SELECTOR ACTUATOR WITH LED BULB

	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs. WITH LED BULB	
	<b>2 Position illuminated selector actuator</b>				
	LED Bulb BA9S type	White LED Bulb / White Lens	P4ASL1LB(S)-2P	528.00	
	24V AC/DC,	Green LED Bulb / Green Lens	P4ASL3LB-2P	333.50	
	110VAC, 110VDC	Red LED Bulb / Red Lens	P4ASL4LB-2P	333.50	
	230VAC, 220VDC	Amber LED Bulb / Amber Lens	P4ASL5LB-2P	333.50	
		Blue LED Bulb / Blue Lens	P4ASL6LB-2P	552.50	
		White LED Bulb / Clear Lens	P4ASL7LB(S)-2P	528.00	
		Yellow LED Bulb / Yellow Lens	P4ASL8LB-2P	333.00	
	<b>Please mention the voltage required after the ordering code</b>				
	LED Bulb BA9S type	White LED Bulb / White Lens	P4ASL1LB(S)-2PSR	528.00	
	24V AC/DC,	Green LED Bulb / Green Lens	P4ASL3LB-2PSR	333.50	
	110VAC, 110VDC	Red LED Bulb / Red Lens	P4ASL4LB-2PSR	333.50	
	230VAC, 220VDC	Amber LED Bulb / Amber Lens	P4ASL5LB-2PSR	333.50	
		Blue LED Bulb / Blue Lens	P4ASL6LB-2PSR	552.50	
		White LED Bulb / Clear Lens	P4ASL7LB(S)-2PSR	528.00	
		Yellow LED Bulb / Yellow Lens	P4ASL8LB-2PSR	333.00	
	<b>LED Bulb</b>	<b>Please mention the voltage required after the ordering code</b>			



MRP w.e.f. 01.11.2021

Control & Signalling Devices 22.5 Ø

CLIP ON PLASTIC SERIES

ILLUMINATED SELECTOR WITH LED BULB

	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs. WITH LED BULB
<b>3 Position Illuminated Selector Actuator</b>				
	Stayput	White LED Bulb / White Lens	P4ASL1LB(S)-3P	541.50
	LED Bulb BA9S type	Green LED Bulb / Green Lens	P4ASL3LB-3P	348.00
	24V AC/DC,	Red LED Bulb / Red Lens	P4ASL4LB-3P	348.00
	110VAC, 110VDC	Amber LED Bulb / Amber Lens	P4ASL5LB-3P	348.00
	230VAC, 220VDC	Blue LED Bulb / Blue Lens	P4ASL6LB-3P	567.00
		White LED Bulb/ Clear Lens	P4ASL7LB(S)-3P	541.50
		Yellow LED Bulb / Yellow Lens	P4ASL8LB-3P	348.00
Please mention the voltage required after the ordering code				
	Momentary	White LED Bulb / White Lens	P4ASL1LB(S)-3PSR	551.50
	LED Bulb BA9S type	Green LED Bulb / Green Lens	P4ASL3LB-3PSR	356.50
	24V AC/DC,	Red LED Bulb / Red Lens	P4ASL4LB-3PSR	356.50
	110VAC, 110VDC	Amber LED Bulb / Amber Lens	P4ASL5LB-3PSR	356.50
	230VAC, 220VDC	Blue LED Bulb / Blue Lens	P4ASL6LB-3PSR	575.50
		White LED Bulb / Clear Lens	P4ASL7LB(S)-3PSR	551.50
		Yellow LED Bulb / Yellow Lens	P4ASL8LB-3PSR	356.50
Please mention the voltage required after the ordering code				
	Momentary / Stayput	White LED Bulb / White Lens	P4ASL1LB(S)-3PSRL	551.50
	LED Bulb BA9S type	Green LED Bulb / Green Lens	P4ASL3LB-3PSRL	356.50
	24V AC/DC,	Red LED Bulb / Red Lens	P4ASL4LB-3PSRL	356.50
	110VAC, 110VDC	Amber LED Bulb / Amber Lens	P4ASL5LB-3PSRL	356.50
	230VAC, 220VDC	Blue LED Bulb / Blue Lens	P4ASL6LB-3PSRL	575.50
		White LED Bulb/ Clear Lens	P4ASL7LB(S)-3PSRL	551.50
		Yellow LED Bulb / Yellow Lens	P4ASL8LB-3PSRL	356.50
Please mention the voltage required after the ordering code				
	Momentary / Stayput	White LED Bulb / White Lens	P4ASL1LB(S)-3PSRR	551.50
	LED Bulb BA9S type	Green LED Bulb / Green Lens	P4ASL3LB-3PSRR	356.50
	24V AC/DC,	Red LED Bulb / Red Lens	P4ASL4LB-3PSRR	356.50
	110VAC, 110VDC	Amber LED Bulb / Amber Lens	P4ASL5LB-3PSRR	356.50
	230VAC, 220VDC	Blue LED Bulb / Blue Lens	P4ASL6LB-3PSRR	575.50
		White LED Bulb / Clear Lens	P4ASL7LB(S)-3PSRR	551.50
		Yellow LED Bulb / Yellow Lens	P4ASL8LB-3PSRR	356.50
LED Bulb	Please mention the voltage required after the ordering code			






MRP w.e.f. 01.11.2021  
Control & Signalling Devices 22.5 Ø



CLIP ON PLASTIC SERIES

TWIN ILLUMINATED ACTUATORS WITH LED

	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs. WITH LED BULB
	<b>Twin Illuminated 1 Flush, 1 Projecting, (IO) Mark</b>			
	LED Bulb, BA9S type 24V AC/DC, 110VAC, 110VDC, 230VAC, 220VDC	Green	P4ATL5LBF3P4 (IO)	278.50
		Red		
		Amber Lens / Amber LED		
	Please mention the voltage required after the ordering code			
	<b>Twin Illuminated Double Flush, (IO) Mark</b>			
	LED Bulb, BA9S type 24V AC/DC, 110VAC, 110VDC, 230VAC, 220VDC	Green	P4ATL5LBF3F4 (IO)	278.50
		Red		
		Amber Lens / Amber LED		
	Please mention the voltage required after the ordering code			
LED Bulb	Please mention the voltage required after the ordering code			

MRP w.e.f. 01.11.2021

Control & Signalling Devices 22.5 Ø

CLIP ON PLASTIC SERIES				
MUSHROOM ILLUMINATED ACTUATORS, LATCHING, WITH LED BULB				
	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs. WITH LED BULB
	<b>Mushroom Illuminated Actuator, Trigger Type, Press to Lock - Turn to release</b>			
	LED Bulb, BA9S type 24V AC/DC, 110VAC, 110VDC, 230VAC, 220VDC	Red	P4ALMLT4LB	507.50
LED Bulb	Please mention the voltage required after the ordering code			
	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs. WITH LED BULB
	<b>Mushroom Illuminated Actuator, Trigger Type, Push to Lock - Pull to release</b>			
	LED Bulb, BA9S type 24V AC/DC, 110VAC, 110VDC, 230VAC, 220VDC	Red	P4ALMPPT4LB	507.50
LED Bulb	Please mention the voltage required after the ordering code			




MRP w.e.f. 01.11.2021

Control & Signalling Devices 22.5 Ø














CLIP ON PLASTIC SERIES

PILOT LIGHTS

	TYPE	COLOUR	ORDERING CODE	PRICE IN Rs. WITH LED BULB
	<b>Pilot Light with LED Bulb</b>			
	LED Bulb, BA9S type 24V AC/DC, 110VAC, 110VDC, 230VAC, 220VDC	White LED Bulb / White Lens	P4PLB1LB(S)	383.00
		Green LED Bulb / Green Lens	P4PLB3LB	188.50
		Red LED Bulb / Red Lens	P4PLB4LB	188.50
		Amber LED Bulb / Amber Lens	P4PLB5LB	188.50
		Blue LED Bulb / Blue Lens	P4PLB6LB	408.50
		White LED Bulb / Clear Lens	P4PLB7LB(S)	383.00
		Yellow LED Bulb / Yellow Lens	P4PLB8LB	188.50
<b>LED Bulb</b>	Please mention the voltage required after the ordering code			

CLIP ON PLASTIC SERIES			
CONTACT ELEMENTS			
	TYPE	ORDERING CODE	PRICE IN Rs.
<b>PANEL MOUNTING</b>			
	NORMALLY OPEN (NO) SILVER CONTACT	C1	63.50
	NORMALLY CLOSED (NC) SILVER CONTACT	C2	63.50
	NORMALLY OPEN (NO) GOLD CONTACT	C3	175.00
	NORMALLY CLOSED (NC) GOLD CONTACT	C4	175.00
<b>BASE MOUNTING</b>			
	NORMALLY OPEN (NO) SILVER CONTACT	C5	63.50
	NORMALLY CLOSED (NC) SILVER CONTACT	C6	63.50
	NORMALLY OPEN (NO) GOLD CONTACT	C7	175.00
	NORMALLY CLOSED (NC) GOLD CONTACT	C8	175.00

## Common types of control and signalling devices Ø 22.5 P4 Clip on series

Description	Type of Actuator or Lense Assembly	Colour of Actuator or Lense	Contact Elements NO = C1 NC = C2 or Lamp Holder	Type of complete Control or Signalling Device	
Flush Pushbutton	P4AF3	Green	1NO	P4PSF310	
	P4AF8	Yellow	2NO+1NC	P4PSF821	
Projecting Pushbutton	P4AP2	Black	2NC	P4PSP202	
	P4AP4	Red	3NO+3NC	P4PSP433	
Booted Pushbutton	P4AF3+2BT7	Green + clear boot	2NO	P4PSF320+2BT7	
	P4AF4+2BT7	Red + clear boot	2NC	P4PSF402+2BT7	
Mushroom Pushbutton Spring return	P4AM2	Black	1NO+1NC	P4PSM211	
	P4AM4	Red	1NC	P4PSM401	
Mushroom Pushbutton latching turn to release	P4AML2	Black	1NC	P4PSML201	
	P4AML4	Red	2NO+2NC	P4PSML422	
Mushroom Pushbutton latching, key to release	P4AMLKB4	Red	1NO+1NC	P4PSMLKB411	
Selector Actuator (2 Pos)	P4AS2-2P	Black	1NO	P4PSS210-2P	
Selector Actuator (3 Pos)	P4AS2-3P	Black	1NO+1NC	P4PSS211-3P	
Key Actuator (2 Pos), key removable in both positions Key Actuator (3 Pos), key removable in left & right positions	P4AK2-2PB		1NO	P4PSK210-2PB	
	P4AK2-3PB		1NO+1NC	P4PSK211-3PB	
Twin Pushbutton marked "I O" Flush - Flush	P4ATF2-F4-IO	Flush-Green Flush-Red	1 NO 1 NC	P4PSTF310-F401-IO	
Flush Illuminated Pushbutton with multichip LED bulb, direct connection	P4ALF3LB24DC	Green	1NO+1NC	P4PSLF3LB1124	
Twin Luminous Pushbutton Without "I O"making Flush - Flush with LED Bulb (240V AC)	P4ATL5LB-F3 -F4230AC	Lense-Amber Flush-Green Flush-Red	1 NO 1 NC	P4PSTL5LBF310-F401230AC	
Pilot Light with LED bulb for 230V AC Bulb: 230V	P4PLLA5	Amber	4LHLB230	P4PLB5LB230	



**GENERAL TERMS AND CONDITIONS**

General Terms : Prices are ex-works Mumbai  
HSN CODE : 85365010 for all the products of this MRP List  
GST : 18%

Prices are subject to revision without notice and ruling at the time of delivery.

This price list supersedes all previous Price Lists.

Warranty Policy : **TEKNIC equipment is guaranteed under the following terms:**

For a period of 12 months from the date of sale, TEKNIC guarantees that its products are free from defects in material and workmanship, with the exception of consumables rendered unserviceable through normal use. During the said period, TEKNIC will replace or repair all parts acknowledged as defective due to factory workmanship and which have been returned in a timely manner by Buyer to TEKNIC and all costs and duties paid, together with a detailed description of the failure and a certified declaration of the number of hours of operation. Repaired or replaced parts will be redelivered FCA (named place) as per INCOTERMS 2000. This warranty is subject to the provision of correct usage, proper maintenance and does not cover defects arising out of fire, faulty operation, accident, inefficient maintenance and willful or accidental damage.

TEKNIC guarantee applies to all equipment, parts and components stored, installed, protected, maintained and used in accordance with TEKNIC specifications and instructions, and respecting the rules for normal use, without any modification by Buyer.

All other conditions or warranties, whether express or implied, relating to the quality and operation of the equipment are excluded, as well as any liability for loss or damage caused directly or indirectly by the equipment or resulting from its use.

Proof of purchase to be provided to avail warranty.

**TEKNIC ELECTRIC (I) PVT. LTD.**

Reg. Office : 116, Hammersmith Industrial Estate, Mahim (W), Mumbai – 400016.  
Head Office : 703/704/705, Madhava, Bandra Kurla Complex, Bandra (E), Mumbai – 400051. Tel : +91-22-42532500  
Works : 65, Marol Co-op. Industrial Estate Ltd., M. Vassanji Road, Andheri (East), Mumbai – 400059. Tel : +91-22-42534500  
Email : [teknico@teknico.co.in](mailto:teknico@teknico.co.in) [mfg@teknico.co.in](mailto:mfg@teknico.co.in) Website : [www.teknico.co.in](http://www.teknico.co.in)